according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

Version Revision Date: SDS Number: Date of last issue: 01.03.2023 26.07.2023 5932811-00015 Date of first issue: 19.05.2020 4.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name **RUDELIM EXPERT 310ML.**

Product code : 0890023702

Product Registration Number : 4313785

Unique Formula Identifier

(UFI)

: 1YR0-D0AU-P002-DR18

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-: Adhesives

Professional use product stance/Mixture

Recommended restrictions

on use

: May only be used by trained personnel.

1.3 Details of the supplier of the safety data sheet

: Würth Danmark A/S Company

Montagevej 6, Industri N2

6000 Kolding

Telephone : +45 7932 3232

Telefax : +45 7556 9710

E-mail address of person

responsible for the SDS

: prodsafe@wuerth.com

1.4 Emergency telephone number

+49 (0)6132 84463 Giftlinjen: +45 82121212

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Respiratory sensitisation, Category 1 H334: May cause allergy or asthma symptoms or

breathing difficulties if inhaled.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

Hazard pictograms :

Signal word : Danger

Hazard statements : H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Precautionary statements : Prevention:

P261 Avoid breathing vapours.
P284 Wear respiratory protection.

Response:

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P342 + P311 If experiencing respiratory symptoms: Call a

POISON CENTER/ doctor.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Hazardous components which must be listed on the label:

4,4'-Diphenylmethane diisocyanate

Additional Labelling

"As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reactive airways dysfunction syndrome).

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

Version SDS Number: Date of last issue: 01.03.2023 Revision Date: 4.1 26.07.2023 5932811-00015 Date of first issue: 19.05.2020

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
4,4'-Diphenylmethane diisocyanate	101-68-8 202-966-0 615-005-00-9 01-2119457014-47	Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Resp. Sens. 1; H334 Skin Sens. 1; H317 Carc. 2; H351 STOT SE 3; H335 STOT RE 2; H373 (Respiratory Tract) specific concentration limit Eye Irrit. 2; H319 >= 5 % STOT SE 3; H335 >= 5 % Skin Irrit. 2; H315 >= 5 % Resp. Sens. 1; H334 >= 0,1 %	>= 0,1 - < 1
Dibutyl hydrogen phosphate	107-66-4 203-509-8	Skin Corr. 1; H314 Eye Dam. 1; H318 Carc. 2; H351 EUH071	>= 0,1 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

Protection of first-aiders First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

If inhaled If inhaled, remove to fresh air.

If not breathing, give artificial respiration.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

If breathing is difficult, give oxygen.

Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty

of water.

Remove contaminated clothing and shoes.

Get medical attention.
Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting.

Get medical attention.

Rinse mouth thoroughly with water.

4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

Respiratory symptoms, including pulmonary edema, may be

delayed.

Excessive exposure may aggravate preexisting asthma and other respiratory disorders (e.g. emphysema, bronchitis, reac-

tive airways dysfunction syndrome).

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically and supportively.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Water spray in large fire situations

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Exposure to combustion products may be a hazard to health.

If the temperature rises there is danger of the vessels bursting

due to the high vapor pressure.

Hazardous combustion prod: :

ucts

Carbon oxides Metal oxides

4/24

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

tective equipment recommendations (see section 8).

6.2 Environmental precautions

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material.

For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

After approximately one hour, transfer to waste container and

do not seal, due to evolution of carbon dioxide.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Avoid breathing vapours.

Do not swallow.

Avoid contact with eves.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Keep container tightly closed. Keep away from water. Protect from moisture.

Already sensitised individuals, and those susceptible

to asthma, allergies, chronic or recurrent respiratory disease, should consult their physician regarding working with respira-

tory irritants or sensitisers.

Take care to prevent spills, waste and minimize release to the

environment.

Hygiene measures : If exposure to chemical is likely during typical use, provide eye

flushing systems and safety showers close to the working place. When using do not eat, drink or smoke. Contaminated work clothing should not be allowed out of the workplace.

Wash contaminated clothing before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Keep in properly labelled containers. Protect from moisture. Store in accordance with the particular national regulations.

Advice on common storage

Do not store with the following product types:

Strong oxidizing agents

Gases

Recommended storage tem- :

perature

0 - 35 °C

7.3 Specific end use(s)

Specific use(s) : No data available

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Di-isononyl phthalate	28553-12-0	GV	3 mg/m3	DK OEL
		S	6 mg/m3	DK OEL
Carbon black	1333-86-4	GV	3,5 mg/m3	DK OEL
	Further information: Means that the substance is included in the list of substances considered carcinogenic.			
		S	7 mg/m3	DK OEL
	Further information: Means that the substance is included in the list of substances considered carcinogenic.			
4,4'-	101-68-8	GV	0,005 ppm	DK OEL
Diphenylmethane diisocyanate			0,05 mg/m3	
	Further inform	nation: Means that th	e substance is included in th	e list of sub-
	stances considered carcinogenic.			
		S	0,01 ppm 0,1 mg/m3	DK OEL
	Further information: Means that the substance is included in the list of substances considered carcinogenic.			
Dibutyl hydrogen	107-66-4	GV	1 ppm	DK OEL
phosphate			8,6 mg/m3	
	Further information: Guiding list of organic solvents.			
		S	2 ppm 17,2 mg/m3	DK OEL
	Further information: Guiding list of organic solvents.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Di-isononyl phthalate	Workers	Inhalation	Long-term systemic effects	51,72 mg/m3
	Workers	Skin contact	Long-term systemic effects	366 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	15,3 mg/m3
	Consumers	Skin contact	Long-term systemic effects	220 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	4,4 mg/kg bw/day
Carbon black	Workers	Inhalation	Long-term local ef- fects	0,5 mg/m3
4,4'-Diphenylmethane diisocyanate	Workers	Inhalation	Long-term local ef- fects	0,05 mg/m3
	Workers	Inhalation	Acute local effects	0,1 mg/m3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

	Consumers	Inhalation	Long-term local effects	0,025 mg/m3
	Consumers	Inhalation	Acute local effects	0,05 mg/m3
Dibutyl hydrogen phosphate	Workers	Inhalation	Long-term systemic effects	1,25 mg/m3
	Workers	Inhalation	Acute systemic effects	5 mg/m3
	Workers	Inhalation	Long-term local ef- fects	1 mg/m3
	Workers	Inhalation	Acute local effects	1 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,44 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	1,78 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	0,31 mg/m3
	Consumers	Inhalation	Acute systemic ef- fects	1,24 mg/m3
	Consumers	Skin contact	Long-term systemic effects	0,22 mg/kg bw/day
	Consumers	Skin contact	Acute systemic effects	0,88 mg/kg bw/day
	Consumers	Ingestion	Long-term systemic effects	0,22 mg/kg bw/day
	Consumers	Ingestion	Acute systemic ef- fects	0,88 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Di-isononyl phthalate	Soil	30 mg/kg
Carbon black	Fresh water	1 mg/l
	Freshwater - intermittent	10 mg/l
	Marine water	0,1 mg/l
	Marine water - intermittent	1 mg/l
4,4'-Diphenylmethane diisocya-	Fresh water	1 mg/l
nate		
	Marine water	0,1 mg/l
	Intermittent use/release	10 mg/l
	Sewage treatment plant	1 mg/l
	Soil	1 mg/kg

8.2 Exposure controls

Engineering measures

Processing may form hazardous compounds (see section 10). Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Eye/face protection : Please follow all applicable local/national requirements when

selecting protective measures for a specific workplace.

Wear the following personal protective equipment:

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

Safety glasses

Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded.

Equipment should conform to DS EN 166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : 0,12 mm

Directive : Equipment should conform to DS EN 374

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Respiratory protection : If adequate local exhaust ventilation is not available or expo-

sure assessment demonstrates exposures outside the rec-

ommended guidelines, use respiratory protection. Equipment should conform to DS EN 14387

Filter type : Combined particulates and organic vapour type (A-P)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : paste

Colour : black

Odour : characteristic

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling

range

270 °C

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Flash point : 164 °C

Auto-ignition temperature : > 300 °C

Decomposition temperature : No data available

pH : substance/mixture is non-soluble (in water)

Viscosity

Viscosity, kinematic : No data available

Solubility(ies)

Water solubility : insoluble

Partition coefficient: n-

octanol/water

Not applicable

Vapour pressure : No data available

Density : 1,19 g/cm³ (20 °C)

Relative vapour density : No data available

Particle characteristics

Particle size : Not applicable

9.2 Other information

Explosives : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Evaporation rate : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

Not classified as a reactivity hazard.

10.2 Chemical stability

Stable if used as directed. Follow precautionary advice and avoid incompatible materials and conditions.

Polymerises at high temperatures with evolution of carbon dioxide.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

10.3 Possibility of hazardous reactions

Hazardous reactions : Isocyanates react with many materials and the rate of reaction

increases with temperature as well as increased contact; these reactions can become violent. Contact is increased by stirring or if the other material mixes with the isocyanate. Exothermic reaction with acids, amines and alcohols Reacts with water to form carbon dioxide and heat

Isocyanates are not soluble in water and sink to the bottom, but react slowly at the interface. The reaction forms carbon

dioxide gas and a layer of solid polyurea.

Hazardous decomposition products will be formed upon con-

tact with water or humid air.

10.4 Conditions to avoid

Conditions to avoid : Exposure to moisture

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

Acids
Bases
Water
Alcohols
Amines
Ammonia
Aluminium
Zinc
Brass
Tin
Copper

Galvanised metals

Humid air

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of:

exposure Skin contact Ingestion

Eye contact

Inhalation

Acute toxicity

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 2,24 mg/l

Exposure time: 1 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Remarks: Based on data from similar materials

Dibutyl hydrogen phosphate:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

Skin corrosion/irritation

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Remarks : Based on data from similar materials

Dibutyl hydrogen phosphate:

Species : reconstructed human epidermis (RhE)

Method : OECD Test Guideline 431

Result : Corrosive after 4 hours or less of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Result : Irritation to eyes, reversing within 7 days Remarks : Based on national or regional regulation.

Dibutyl hydrogen phosphate:

Species : Rabbit

Result : Irreversible effects on the eye

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Components:

4,4'-Diphenylmethane diisocyanate:

Test Type : Buehler Test
Exposure routes : Skin contact
Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Exposure routes : Inhalation Species : Rat : positive

Remarks : Based on data from similar materials

Assessment : Probability of respiratory sensitisation in humans based on

animal testing

Dibutyl hydrogen phosphate:

Test Type : Maximisation Test Exposure routes : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

Germ cell mutagenicity

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Rat

Application Route: inhalation (dust/mist/fume)

Method: OECD Test Guideline 474

Result: negative

Dibutyl hydrogen phosphate:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

Test Type: Chromosome aberration test in vitro

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay) Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Species : Rat

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 Years Result : positive

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

ment

Limited evidence of carcinogenicity in animal studies

Dibutyl hydrogen phosphate:

Species : Rat
Application Route : Ingestion
Exposure time : 24 month(s)
Result : positive

Remarks : Based on data from similar materials

Carcinogenicity - Assess-

ment

Limited evidence of carcinogenicity in animal studies

Reproductive toxicity

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Effects on foetal develop- : Test Type: Embryo-foetal development

ment Species: Rat

Application Route: inhalation (dust/mist/fume)

Result: negative

Remarks: Based on data from similar materials

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

Dibutyl hydrogen phosphate:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Effects on foetal develop-

ment

Test Type: Embryo-foetal development

Species: Rat

Application Route: Ingestion

Result: negative

STOT - single exposure

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

4,4'-Diphenylmethane diisocyanate:

Exposure routes : inhalation (dust/mist/fume)

Target Organs : Respiratory Tract

Assessment : Shown to produce significant health effects in animals at con-

centrations of >0.02 to 0.2 mg/l/6h/d.

Dibutyl hydrogen phosphate:

Assessment : No significant health effects observed in animals at concentra-

tions of 100 mg/kg bw or less.

Repeated dose toxicity

Components:

4,4'-Diphenylmethane diisocyanate:

 Species
 : Rat

 NOAEL
 : 0,2 mg/m3

 LOAEL
 : 1 mg/m3

Application Route : inhalation (dust/mist/fume)

Exposure time : 2 yr

Remarks : Based on data from similar materials

Dibutyl hydrogen phosphate:

Species : Rat

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

NOAEL : 30 mg/kg
LOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 40 - 50 Days

Method : OECD Test Guideline 422

Aspiration toxicity

Not classified based on available information.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

4,4'-Diphenylmethane diisocyanate:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 3.000 mg/l

Exposure time: 96 h

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 129,7 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): > 1.640

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

NOEC (Desmodesmus subspicatus (green algae)): 1.640 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Toxicity to microorganisms : EC50 : > 100 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Remarks: Based on data from similar materials

Toxicity to daphnia and other : NOEC: 10 mg/l

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

aquatic invertebrates (Chron-

ic toxicity)

Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Remarks: Based on data from similar materials

Dibutyl hydrogen phosphate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

ErC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l

Exposure time: 72 h

Method: Directive 67/548/EEC, Annex V, C.3.

EC10 (Desmodesmus subspicatus (green algae)): 76 mg/l

Exposure time: 72 h

Method: Directive 67/548/EEC, Annex V, C.3.

Toxicity to microorganisms : EC50 : > 10.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 66 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

4,4'-Diphenylmethane diisocyanate:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 302

Remarks: Based on data from similar materials

Dibutyl hydrogen phosphate:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 12 % Exposure time: 28 d

Method: Directive 67/548/EEC Annex V, C.4.E.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

12.3 Bioaccumulative potential

Components:

4,4'-Diphenylmethane diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 200

Partition coefficient: n-

octanol/water

log Pow: 4,51

Dibutyl hydrogen phosphate:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): < 7

Partition coefficient: n-

octanol/water

log Pow: < 4

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Waste, residues, etc. must be collected, stored and disposed

of in tightly closed container labeled: "Contains a substance that is covered by the Danish health and safety regulation in

terms of cancer risk."

Dispose of in accordance with local regulations.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Waste codes should be assigned by the user, preferably in

discussion with the waste disposal authorities.

Do not dispose of waste into sewer.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

If not otherwise specified: Dispose of as unused product.

Waste Code : The following Waste Codes are only suggestions:

used product

08 04 09, waste adhesives and sealants containing organic

solvents or other hazardous substances

08 05 01, waste isocyanates

unused product

08 04 09, waste adhesives and sealants containing organic

solvents or other hazardous substances

08 05 01, waste isocyanates

uncleaned packagings

15 01 10, packaging containing residues of or contaminated

by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

IATA : UN 3334

14.2 UN proper shipping name

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Aviation regulated liquid, n.o.s.

(4,4'-Diphenylmethane diisocyanate)

14.3 Transport hazard class(es)

ADN : Not regulated as a dangerous good

ADR : Not regulated as a dangerous good

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

RID : Not regulated as a dangerous good

IMDG : Not regulated as a dangerous good

Class Subsidiary risks

IATA : 9

14.4 Packing group

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

964

IATA (Cargo)

Packing instruction (cargo :

aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

IATA (Passenger)

Packing instruction (passen: 964

ger aircraft)

Packing instruction (LQ) : Y964
Packing group : III

Labels : Miscellaneous

14.5 Environmental hazards

ADN : Not regulated as a dangerous good
ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered: Number on list 75, 3

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

If you intend to use this product as tattoo ink, please contact your vendor.

dor.

Di-isononyl phthalate (Number on

list 52)

4,4'-Diphenylmethane diisocyanate

(Number on list 74, 56)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

MAL-Code-Number : 3-6 (1993)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 0 %, 0 g/l

Remarks: VOC content excluding water

Other regulations:

When evaluating a workplace, measures must be taken to ensure that employees are not exposed to conditions that may pose a risk during pregnancy or breastfeeding (cf. The Danish Working Environment Authority's Executive Order on The Performance of Work)

Young people under the age of 18 are not allowed to use or be exposed to the product professionally. Young people above the age of 15 are, however, except from this rule if the product is a necessary part of their education.

Users must have undergone approved training to work with epoxy components and isocyanates.

Persons suffering from asthma or eczema and people who have found chronic lung diseases or recorded skin or respiratory allergies to isocyanates, must not work with the material.

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

Version Revision Date: SDS Number: Date of last issue: 01.03.2023 26.07.2023 5932811-00015 Date of first issue: 19.05.2020 4.1

Persons with excessive perspiration (hyperhidrosis manuum) must not work with the material.

The substance/mixture is subject to the provisions of BEK nr. 1795 of 18/12/2015 (as amended) "Executive order on Measures to Protect Workers from the Risks related to Exposure to Carcinogenic Substances and Materials at Work". The work with this substance/mixture may pose a cancer risk.

: 4,4'-Diphenylmethane diisocyanate

15.2 Chemical safety assessment

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

Other information Items where changes have been made to the previous version

are highlighted in the body of this document by two vertical

lines.

Full text of H-Statements

H314 Causes severe skin burns and eye damage.

Causes skin irritation. H315

H317 May cause an allergic skin reaction. : Causes serious eye damage. H318 Causes serious eye irritation. H319

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficul-

ties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated

exposure if inhaled.

EUH071 Corrosive to the respiratory tract.

Full text of other abbreviations

Acute Tox. Acute toxicity Carc. Carcinogenicity Eye Dam. Serious eye damage

Eve Irrit. Eve irritation

Respiratory sensitisation Resp. Sens.

Skin Corr. Skin corrosion Skin Irrit. Skin irritation Skin sensitisation Skin Sens.

Specific target organ toxicity - repeated exposure STOT RE Specific target organ toxicity - single exposure STOT SE Denmark. Occupational Exposure Limits DK OEL

DK OEL / S Exposure period of 15 minutes DK OEL / GV Long term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Test-

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020

ing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances: (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice : Observe requirements and guidance related to training before

using this product at work.

Sources of key data used to compile the Safety Data

Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Classification of the mixture: Classification procedure:

Resp. Sens. 1 H334 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

DK / EN

according to Regulation (EC) No. 1907/2006, as amended by Commission Regulation (EU) 2020/878



RUDELIM EXPERT 310ML.

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 01.03.2023

 4.1
 26.07.2023
 5932811-00015
 Date of first issue: 19.05.2020